



## FTW210 – Solid Drilled Flanged Thermowell & Coating

FTW210

<b>Flange Size</b>	
1"	1
1 ½"	15
2"	2
2 ½"	25
DN25	D25
DN40	D40
DN50	D50
DN80	D80
<b>Flange Rating</b>	
150lb	150
300lb	300
600lb	600
900lb	900
1500lb	1500
PN16	P16
PN25	P25
PN40	P40
<b>Flange Type</b>	
Raised Face	RF
Flat Face	FF
Ring Type Joint	RJ
<b>Construction</b>	
Seal Welded	1
Full Penetration Welded	2
One Piece Forged	3
<b>Heat Treatment</b>	
NACE MR0175/ISO 15156	HT
None	X
<b>Immersion Length (U)</b>	
Xmm	X
<b>Stem Ø (S)</b>	
Xmm	X
<b>Bore Ø (B)</b>	
6.5mm	6.5
Xmm	XX
<b>Tip Thickness</b>	
5mm	5
Xmm	X
<b>Lagging (T)</b>	
50mm	50
Xmm	XX
<b>Material</b>	
304/304L Stainless Steel	304
310 Stainless Steel	310
316/316L Stainless Steel	316
Alloy C276	276
Alloy 400	400
Alloy 600	600
Alloy 601	601
Alloy 625	625
Alloy 800	800
<b>Instrument Connection – Thread Size</b>	
¼"	14
½"	12
¾"	34
1"	1
<b>Instrument Connection - Thread Type</b>	
BSPP	BP
BSPT	BT
NPT	NT

---

**Coated Wetted Parts**

FEP

Tantalum

**F**  
**T**

**Example Ordering Code:**

FTW210-2-300-RF-1-X-150-26.5-20-6.5-5-50-316-12-NT-T