




TWA501 – Thermocouple Sensor with Fabricated Weld In Thermowell

TWA501

Sensor Configuration	
Simplex	S
Duplex	D
Triplex	T
Sensor Type	
Type E	E
Type J	J
Type K	K
Type N	N
Type T	T
Sensor Junction	
Isolated	I
Grounded	G
Exposed	E
Sheath Material	
310 Stainless Steel	310
316 Stainless Steel	316
Alloy 600	600
Approvals	
ATEX/IECEX Exia II 1 GD	IA
ATEX/IECEX Exd II 2 GD	XD
None	X
Connection Head	
Type 11 (Aluminium)	11
Type 16 (Aluminium)	16
Type 44 (316 Stainless Steel)	44
Type 46W (Plastic)	46W
Type 55/A (Aluminium)	55A
Type 55/S (316 Stainless Steel)	55S
Termination	
150mm Tails	TA
Ceramic Terminal Block	TB
HS4200 Temperature Transmitter	42
HS4400 Temperature Transmitter (Exia)	44
HS4600 Temperature Transmitter (Exia, HART)	46
HS5500 Temperature Transmitter & Indicator (HART)	55
HS5600 Temperature Transmitter & Indicator (Exia, HART)	56
Indicator	
HS3300	33
HS3700 (Battery Powered)	37
HS5500 Temperature Transmitter & Indicator (HART)	55
HS5600 Temperature Transmitter & Indicator (Exia, HART)	56
None	X
Extension	
Nipple & Locknut	NL
Nipple Union Nipple	NU
None	X
Extension Length (N)	
50mm	50
75mm	75
100mm	100
150mm	150
Xmm	X
None	X
Boss Ø	
Xmm	X
Chamfer Angle (A°)	
45°	45
X°	X
Immersion Length (U)	
Xmm	X

H&B Sensors Ltd | Odyssey House | Durban Road | Bognor Regis | West Sussex | PO22 9RH | UK

Tel: +44(0)1243 866866 | Email: info@hbsensors.com | hbsensors.com

Registration # 1448023 (England & Wales) | VAT # GB321828666

Stem Ø (S)	
Xmm	X
Lagging (T)	
50mm	50
Xmm	X
Material	
304/304L Stainless Steel	304
310 Stainless Steel	310
316/316L Stainless Steel	316
Alloy C276	276
Alloy 400	400
Alloy 600	600
Alloy 601	601
Alloy 625	625
Alloy 800	800

Example Ordering Code:

TWA501-S-K-I-316-X-11-42-X-NL-75-25.4-45-150-10-50-316